




WI-CPE900-KIT
5.8GHz 900Mbps
Outdoor CPE for wireless CCTV
Data sheet

Highlights

- 500mW High power output, coverage up to 10KM for PTP and PTMP application to carry 50pcs 1080P camera
- auto-connect for PTP/PTMP application, no need setting software
- Wireless Ac speed up to 900Mbps
- Support open frequency from 4920 to 6100 MHz
- Inside 60 degree 20dBi Directional Antenna Technology
- 27dBm High-Power design
- 2x2 MIMO Technology
- 48V PoE Adapter supports up to 100 meter
- 1 PoE Port design,1 LAN port
- Qualcomm AR9344 600MHz Chipset,64MB RAM
- 10KV Lightning Protection
- Super TDMA Technology

Tx Power Specs				Rx Power Specs			
	Data Rate	Tx Power	Tolerance		Data Rate	Sensitivity	Tolerance
802.11a	6-24 Mbps	27 dBm	±2dB	802.11a	6-24 Mbps	-94 dBm	±2dB
	36 Mbps	25 dBm	±2dB		36 Mbps	-82 dBm	±2dB
	48 Mbps	23 dBm	±2dB		48 Mbps	-79 dBm	±2dB
	54 Mbps	23 dBm	±2dB		54 Mbps	-76 dBm	±2dB
802.11n	MCS0	27 dBm	±2dB	802.11n	MCS0	-93 dBm	±2dB
	MCS1	27 dBm	±2dB		MCS1	-88 dBm	±2dB
	MCS2	27 dBm	±2dB		MCS2	-86 dBm	±2dB
	MCS3	27 dBm	±2dB		MCS3	-82 dBm	±2dB
	MCS4	26 dBm	±2dB		MCS4	-80 dBm	±2dB
	MCS5	24 dBm	±2dB		MCS5	-75 dBm	±2dB
	MCS6	23dBm	±2dB		MCS6	-73 dBm	±2dB
	MCS7	23 dBm	±2dB		MCS7	-72 dBm	±2dB
	MCS8	27 dBm	±2dB		MCS8	-93 dBm	±2dB
	MCS9	27 dBm	±2dB		MCS9	-89 dBm	±2dB
	MCS10	27 dBm	±2dB		MCS10	-87 dBm	±2dB
	MCS11	27 dBm	±2dB		MCS11	-82 dBm	±2dB
	MCS12	26 dBm	±2dB		MCS12	-81 dBm	±2dB
	MCS13	24 dBm	±2dB		MCS13	-75 dBm	±2dB
	MCS14	23 dBm	±2dB		MCS14	-73 dBm	±2dB
MCS15	23 dBm	±2dB	MCS15	-72 dBm	±2dB		



Product



Description

Wi-Tek's WI-CPE900-KIT is a 5GHz 900Mbps 2x2 MIMO outdoor wireless CPE based on 802.11AC technology. It is high performance, cost-effective and dedicated to long

distance wireless CCTV network solutions. Featuring the revolutionary Wi-Tek technology in firmware design and 20dBi directional dual-polarized antenna, WI-CPE900 is specialized designed for long distance wireless data transmission, wireless coverage extension and other industrial wireless solutions. is widely used in various fields of communication:

- ◆ Point-to-point,Point-to-multipoint wireless communication
- ◆ Wireless Video Surveillance
- ◆ Enterprise wireless LAN interconnection
- ◆ Mobile operators WISP large customer access system
- ◆ Wi-Fi Wireless city coverage

Typical Applications



Specifications

HARDWARE FEATURES	
Processor	Qualcomm AR9344
Memory	64MB SDRAM 8MB Flash
Interface	1X10/100/1000 PoE Interface 1X10/100 LAN Interface
Power Supply	48V PoE Adapter Included
Power Consumption	8W
Dimensions (H x W x D)	260x100x60mm
Antenna Type	Built-in 20dBi Dual-polarized Antenna Horizontal beam width: 60degree Vertical beam width: 15degree
Protection	10KV Lightning Protection
Enclosure	Outdoor UV Stabilized Plastic IP65 waterproof Certification

WIRELESS FEATURES	
Wireless Standards	802.11ac
Protocol	CSMA/CA,TCP/IP,IPX/SPX, NetBEUI, DHCP TDMA
Wireless Mode	AP,Client
Wireless Speeds	11a:54M,48M,36M,24M,18 M,12M,9M,6Mbps 11n:6.5M, 13M, 13.5M, 19.5M, 26M, 27M, 39M, 40.5M, 52M, 54M, 58.5M, 65M, 81M, 108M, 121.5M, 135M, 150M, 270M, 300Mbps
Frequency	4920-6100MHz
Transmission Power	27dBm(500mW)

SOFTWARE FEATURES

SOFTWARE FEATURES

Wireless Configurations

802.11ac Modes
Selectable Channel Width:
20/40MHz
Automatic Channel
Selection
Transmission Power
Control
Dynamic Frequency
Selection (DFS)
WDS Enable/Disable
Security: WPA/WPA2,
WPA-PSK/WPA2-PSK
(AES/TKIP) Encryption,
64/128/152-bit WEP
Encryption
SSID Broadcast
Enable/Disable
Distance/ACK Timeout
Setting
Wireless MAC Address
Filter
Wireless Advanced:
> Beacon Interval/RTS
Threshold/Fragmentation
>Threshold/DTIM
Interval/AP Isolation/Short
GI/Wi-Fi Multimedia

Management

WEP management

System-level Optimizations

Optimized IGMP
Snooping/Proxy for
multicast applications

SOFTWARE FEATURES	
	Hardware watch dog

OTHERS	
Certification	CE
Package Contents	1*CPE 1*PoE Adapter 1* Pole Mounting Kit included
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 10, Windows 8, Windows 7, MAC OS, NetWare, UNIX or Linux. Note: We recommend you to use one of following Web browsers for an improved user experience: Google Chrome, Safari, and Firefox. IE browsers are not recommended.
Environment	Working Temp: -40 ~ 70°C Storage Temp: -40 ~85°C Working Humidity: 10%~95% non-condensing